


PRODUCT SHEET
Trunk
Art. no: CFL-1535-30WD-08-3

Trunk



Unit: mm





IP20 230V 50Hz A++

SPECIFICATIONS	
Lyskilde :	LED (innebygget)
Systemeffekt [W]:	35W
Fargetemperatur [K]:	3000K
Fargegjengivelse [CRI/Ra]:	80
Lumen ut (lm):	5443lm
Lumen LED (tc=25):	5600lm
Spredningsvinkel [°]:	90°
Optikk:	Klar
Dimmetype:	Ingen
Spenning [V]:	230V 50Hz
Tilkobling:	Trunk 8-leder
Montering:	Nedhengt, Tak
Forventet Levetid :	L80B50: 60 000h
Lumen/W:	155lm/W
Farge :	Hvit
Lengde [mm]:	1500mm
Høyde [mm]:	78,6mm
Bredde [mm]:	72,3mm
Vekt [kg]:	1,64kg

Trunk is a premium quality and highly advanced linear pendant light system offering
continuous light distribution. We offer a variety of accessories securing easy installation
and various layouts ensuring a natural like lighting to any area. The Trunk light fixtures
are manufactured in ultra-thin steel plates securing a long-life product. The Trunk fixtures
are delivered with all needed installation details in one box and no tools are needed for
the installation. Please see technical table below for detailed information. Batteries for emergency: 1 year warranty