

Designed by Robert Dudley Best

PRODUCT



COLOURS



// Charcoal black / Brass // Grey / Brass



// Matt-White / Brass // All Brass



// Bone China / Brass

Don't polish the brass

DESCRIPTION

Bestlite has been in continuous production since 1930. Robert Dudley Best created Bestlite design. He was highly influenced by the Bauhaus. In the past 80 years, people appreciated the lamps and it decorates many homes, hotels and restaurants worldwide. Loved by architects, designers and design aficionados throughout its 80-year history, today, Bestlite enjoys global iconic status.

VERSION - BESTLITE WALL LAMP BL7

Shade: Charcoal black, Matt-White, Grey, Brass, or Bone China
 Tube, arm, and foot base: Brass with lacquered surface
 Fabric wire - Brass colour

RAL codes are indicative.

- Charcoal black/Brass / White inside // RAL 9011 / RAL 9003 // Gloss level 10 / Gloss level 20
- Grey/Brass / White inside // RAL 2604005 / RAL 9003 // Gloss level 10 / Gloss level 20
- Brass/Brass / White inside // - / RAL 9003 // - / Gloss level 20
- Matt-White/Brass / White inside // RAL 9003 / RAL 9003 // Gloss level 10 / Gloss level 20
- Glossy Bone China/Brass

Please contact us for other colours or finishes.

VERSION

Order item - look for part number in the pricelist.

Series contains the following:

BL5, BL6, BL7, BL10

FACTS

MEASUREMENT - L X W X H inches

Lamp height: 11,4 inches
 Tube length: -
 Shade height: 5,5 inches
 Shade diameter: Ø6,3 inches
 Cord - total length w/sw: App. 94,5 inches
 Cord - exposed out of lamp: App. 78,7 inches

WEIGHT ITEM - LAMP INCL. WIRE

489 g

PACKAGING TYPE

White cardboard box w/ 5ply corrugated

PACKAGING MEASUREMENT - L X W X H inches

L:10,2 x W:11 x H: 7,87 inches

WEIGHT PACKAGING - MATERIAL TYPE

- Paper Egg crate: 280,5 g
- PE polybag: 60 g
- Cardboard inside: 26 g
- Cardboard outside: 206 g

WEIGHT PACKAGING - TOTAL

1001 g

NUMBER OF PARCELS

1 pcs.

LIGHT SOURCE

- Socket: E12 base
- Recommended light source: *All LED and fluorescent light bulbs*
- Recommended wattage: 9 W = (40 WATT incandescent bulbs)
- Max wattage: 13 W
- Recommended light source: *Halogen light bulb*
- Recommended wattage: 28 W = (40 WATT incandescent bulbs)
- Max wattage: 30 W

- All lamps can be fitted with a dimmer.
 Please contact your local electrician.

- Lightbulb not included

CLEANING AND MAINTENANCE

Use a soft damp cloth when cleaning your Bestlite lamp. Do not use household cleaners.

ACCESSORIES

-

ENVIRONMENT


-

TESTS

-

CERTIFICATION AND LABELS

CUL-APPROVED



STANDARD - (* = Standard for each country/region)

STOCK - BL7* Hard-wired (switched):
No cord, switch on wallbracket

- US voltage: 120 V
- Frequency: 60 Hz
- Supply voltage: AC power ~
- Normally Closed: IP20



UL listed

KOMPONENTS

- 01 // Shade Ø16 cm.
- 05 // E14 lamp holder
- 10 // Insulating ring
- 11 // Internal shade ring
- 12 // External shade ring
- 13 // Lamp holder cover
- 15 // Universal joint
- 17 // Bestlite arm
- 41 // Push button switch
- 42 // Cover for push button switch
- 46 // Wall bracket
- 49 // Screw 9x19 mm.
- 51 // Mounting plate Ø7 cm

MATERIAL

Shade: Charcoalblack, White or Grey
Tube and arm: Brass with lacquered surface
Textile covered cord

Shade and base: Brass with lacquered surface
Tube and arm: Brass with lacquered surface
Textile covered cord

INSTALLATION INSTRUCTIONS

Instructions document: No. 10-20-006-01.

The Bestlite key:

It's a practical tool that enables you to fasten the lamp arm. Simply use it like a screwdriver in the slot in the Bestlite nut.

Technical information:

Light source: CAUTION TO REDUCE THE RISK OF FIRE, USE MAX. 40 WATT (INCANDESCENT, E27 type B bulbs, 220V 60Hz AC ONLY). Alternatively max. 30W halogen bulbs. Turn power off when changing light bulb.

The lamp is not approved for outdoor use or use in damp/wet rooms.

Some advice on cleaning your Bestlite:

Powder coated parts - base/bracket and shade:
Wipe the parts with a damp cloth (soaked in warm water) and a bit of mild detergent.

Chrome plated parts:
Wipe the parts with a damp cloth and wipe dry to bring up lustre. If the surface is stuck use a metal polish made especially for chromium or other soft metals. Use only soft cloth for wiping and polishing, never sponges or steel wool.

Do not use abrasive household cleaners.
Do not use acidic or alkaline cleaning materials, glass cleaner or household ammonia.

Dear Bestlite customer,
Congratulations on your Bestlite!

You have chosen a genuine design classic, which has been in continuous production for more than 75 years.

On the other side of this leaflet you will find some useful instructions for the use of your Bestlite.

Should you have any questions, please feel free to e-mail us at gubi@gubi.com or visit us at www.gubi.com.

Best regards,
Bestlite

001-07300

1: Shade
2: Bracket
3: Internal ring
4: Light bulb

The shade fits and swivels.

Wall mounting:
Choose an angled mark the spot carefully. Pre-drilling and use of plugs in the wall is recommended. Mount the plate (1) - make sure you use appropriate screws and plugs for most wall in this plate carries the weight of the lamp. When the plate is fastened to the wall - attach the wire by connecting the cap and lamp firmly onto the plate.

The wall mounting plate:
Two holes, above and below, for wall mounting. Use the provided screws (see the note on screws). Position of these two holes should always be horizontal. Mounting the plate as shown is important since the light is fairly bright if the plate is slanted.

Connect the lamp wire to the supply wires (2):
Be sure to connect all grounding wires (green) to the side wire (not steel) and safety connections are not in the box with the lamp. Tuck wires carefully inside the base of the lamp and secure the lamp on the wall bracket.

Repeat steps 1-5 with the lamp to the wall.
Repeat steps 1-5 with the lamp to the wall. Be careful not to connect any wires and wires to the light of the lamp. Use the provided screws to secure the lamp to the wall.

Place light bulb in lamp and turn (4) the power on.