



MASTER PL-C 2 Pin

MASTER PL-C 18W/830 /2P 1CT/5X10BOX

MASTER PL-C is an efficient medium-wattage compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base.

Product data

General Information	
Cap-Base	G24D-2 [G24d-2]
Life to 10% Failures (Nom)	6500 h
Life to 50% Failures (Nom)	10000 h
LSF 2000 h Rated	99 %
LSF 4000 h Rated	98 %
LSF 6000 h Rated	92 %
LSF 8000 h Rated	78 %

Light Technical	
Color Code	830 [CCT of 3000K]
Luminous Flux (Nom)	1200 lm
Luminous Flux (Rated) (Nom)	1200 lm
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	67 lm/W
Color Rendering Index (Nom)	82
LLMF 2000 h Rated	92 %
LLMF 4000 h Rated	87 %
LLMF 6000 h Rated	83 %
LLMF 8000 h Rated	81 %

Operating and Electrical	
Power (Rated) (Nom)	17.9 W
Lamp Current (Nom)	0.230 A

Temperature	
Design Temperature (Nom)	28 °C

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Cap-Base Information	2 Pins

Approval and Application	
Energy Efficiency Label (EEL)	B
Mercury (Hg) Content (Nom)	1.4 mg
Energy Consumption kWh/1000 h	22 kWh

Product Data	
Full product code	871150062091070
Order product name	MASTER PL-C 18W/830 /2P 1CT/5X10BOX
EAN/UPC - Product	8711500620910

MASTER PL-C 2 Pin


Order code	927905783040
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	927905783040

Net Weight (Piece)	57.800 g
ILCOS Code	FSQ-18/30/1B-I-G24d=2

Warnings and Safety

- Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.



Dimensional drawing



Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-C 18W/830 /2P	27.1 mm	27.1 mm	109.5 mm	128.0 mm	150.4 mm
1CT/5X10BOX					

PL-C 18W/830/2P

Photometric data



Lightcolor /830

Lightcolor /830

MASTER PL-C 2 Pin

Lifetime



Life Expectancy 3 h cycle



Life Expectancy 12 h cycle

Lumen Maintenance 3h + 12 h cycle

