



PRODUCT SHEET

Driver 700mA cc 12W (9-18V) Phasecut AcTec SM&JB

Art. no: D70012NT-02

Ledpro
by NORLUX

Driver 700mA cc 12W (9-18V) Phasecut AcTec SM&JB



Dimbar LED driver for konstant strøm (700mA) 12W.
Leveres med junction boks for enklere montering
Faseavsnitt dim.



SPECIFICATIONS

System Effekt [W]:	12W
Dimming:	Phase-Cut
CC eller CV:	CC
CC [mA]:	700 - mA
CC (driver spenning ut) [V]:	9 - 18V
Maks Spenning ut [V]:	26
Strøm Toleranse [%]:	5%
Strøm Ripple [%]:	50%
Forventet Levetid:	30000h
Spenning [V]:	230V 50Hz V
Isolasjonsklasse:	2
Dimming Minimum Level :	1%
Dimming Phasecut Type:	Leading / Trailing edge
Maks belastning per kurs - B10:	35
Maks belastning per kurs - B16:	56
Maks belastning per kurs - C10:	74
Maks belastning per kurs - C16:	118
Lekkasjestrøm [mA]:	0,7mA
Startstrøm I _{max} [A]:	5A
Startstrøm tid [μs]:	300μs
Produsent:	AcTEC
Tilkobling Sekundær:	SM kontakt
Lengde:	109mm
Høyde:	22mm
Bredde:	40mm
Vekt:	0,07kg