



## PRODUCT SHEET

Driver On/Off 500mA max 21W 25-42V 18i3 Male/ EPN0034

Art. no: 0300-08

**Ledpro**  
by NORLUX

# Driver On/Off 500mA max 21W 25-42V 18i3 Male/ EPN

Tridonic On/Off driver innstilt på 500mA, max 21W.

Primær side 0,3m kabel med 18i3 (male)

Sekundær side EPN0034 (female).



| SPECIFICATIONS                   |                     |
|----------------------------------|---------------------|
| System Effekt [W]:               | 21W                 |
| Dimming:                         | Ingen               |
| CC eller CV:                     | CC                  |
| CC [mA]:                         | 500 - mA            |
| CC (driver spenning ut) [V]:     | 25 - 42V            |
| Maks Spenning ut [V]:            | 60                  |
| Strøm Toleranse [%]:             | 7,5%                |
| Strøm Ripple [%]:                | 5%                  |
| Strøminnstilling:                | ADV Plug (Tridonic) |
| Forventet Levetid:               | 100000h             |
| Spenning [V]:                    | 230V 50Hz V         |
| Isolasjonsklasse:                | 1 or 2              |
| Maks belastning per kurs - B10:  | 14                  |
| Maks belastning per kurs - B16:  | 24                  |
| Maks belastning per kurs - C10:  | 24                  |
| Maks belastning per kurs - C16:  | 40                  |
| Lekkasjestrøm [mA]:              | 0,45mA              |
| Startstrøm I <sub>max</sub> [A]: | 25A                 |
| Startstrøm tid [μs]:             | 200μs               |
| Produsent:                       | Tridonic            |
| Tilkobling Primær:               | 18i3 hunn           |
| Tilkobling Sekundær:             | EPN0034 hunn        |
| Lengde:                          | 157mm               |
| Høyde:                           | 30mm                |
| Bredde:                          | 43mm                |
| Vekt:                            | 0,2kg               |