



PRODUCT SHEET

Driver Phasecut 900mA Panel max 45W 25-50V 18i3 Male/EPN0034

Art. no: 0300-26

Ledpro
by NORLUX

Driver Phasecut 900mA Panel max 45W 25-50V 18i3 M

Fasekutt driver for Panel

Max 45W

900mA

22-40V

Primærside 18i3 male kobling

Sekundærside EPN0034 kobling



SPECIFICATIONS

System Effekt [W]:	45W
Dimming:	Fasekutt
CC eller CV:	CC
CC [mA]:	900 - mA
CC (driver spenning ut) [V]:	25 - 50V
Maks Spenning ut [V]:	60
Strømminnstilling:	Ingen
Spenning [V]:	230V 50Hz V
Isolasjonsklasse:	2
Dimming Minimum Level :	1%
Dimming Phasecut Type:	Leading / Trailing edge
Maks belastning per kurs - B10:	35
Maks belastning per kurs - B16:	56
Maks belastning per kurs - C10:	74
Maks belastning per kurs - C16:	118
Startstrøm I _{max} [A]:	5A
Startstrøm tid [µs]:	300µs
Produsent:	AcTEC
Produsent P/N:	D90045NT - Driver 900mA cc 45W Phasecut
Tilkobling Primær:	18i3 hunn
Tilkobling Sekundær:	EPN0034 hunn
Farge :	Hvit
Lengde:	166mm
Høyde:	24mm
Bredde:	52mm
Vekt:	0,2kg
Omgivelsestemperatur [°C]:	-20 - 50