



FDV SPEC SHEET

Kronos 2800lm Asymmetrical 840 15,9W WH 1140mm DALI

Art. no: 101630-3-ddd

Ledpro
by NORLUX



Kronos 2800lm Asymmetrical 840 15,9W WH 1140mm



Art. no: 101630-3-ddd

LYS TEKNISK

Lumen LED (tc=25):	2800
Spredningsvinkel [°]:	70°40°
Fargetemperatur [K]:	4000
Fargegjengivelse [CRI/Ra]:	80
Fargekode:	840
Fargetoleranse [SDCM]:	3

MONTERING / TILKOBLING

Tilkobling:	Terminal
Montering:	Nedhengt, Vegg

PRODUKT

IP-grad:	IP40
Vandal klasse:	IK05
Driftstemperatur [°C]:	0 - 35
Farge :	Hvit
Lengde [mm]:	1140
Høyde [mm]:	68
Bredde [mm]:	60
Vekt [kg]:	2

ELEKTRISK DATA

Dimmetype:	DALI
Dimming Output Type:	Amplitude Modulation
Flicker metric (Pst LM) <:	0,02
Stroboscopic effect metric (SVM) <	0,01
Systemeffekt [W]:	15,9
Spenning [V]:	230V 50Hz
Isolasjonsklasse:	1
Maks belastning pr kurs - B10:	20
Maks belastning pr kurs - B16:	33
Maks belastning pr kurs - C10:	34
Maks belastning pr kurs - C16:	56
Startstrøm I _{max} [A]:	25
Startstrøm tid [µs]:	177
Sokkel :	N/A
Spenning LED Min [V]:	54,4
Spenning LED Max [V]:	55,6