



PRODUCT SHEET

Driver 350-1050mA cc LCA 75W 350-1050mA one4all lp PRE DALI

Art. no: 28000659



Driver 350-1050mA cc LCA 75W 350-1050mA one4all l

Forward voltage is dependent of current setting. See manufacture datasheet for complete details.



SPECIFICATIONS

System Effekt [W]:	75W
Dimming:	Corridor, DALI2, Push, Ready2Mains
CC eller CV:	CC
CC [mA]:	350 - 1050mA
CC (driver spenning ut) [V]:	40 - 110V
Maks Spenning ut [V]:	250
Strøm Toleranse [%]:	3%
Strøm Ripple [%]:	2,5%
Strøminnstilling:	DALI-2, I-Select 2 Plug (Tridonic), Ready2Ma
Forventet Levetid:	100000h
Spenning [V]:	230V 50Hz / 176-275VDCV
Isolasjonsklasse:	1 or 2
Maks belastning per kurs - B10:	9
Maks belastning per kurs - B16:	14
Maks belastning per kurs - C10:	15
Maks belastning per kurs - C16:	23
Lekkasjestrøm [mA]:	0,65mA
Startstrøm I _{max} [A]:	40A
Startstrøm tid [µs]:	178µs
Produsent:	Tridonic
Produsent P/N:	28000659- Driver 350-1050mA cc LCA 75W 3
Lengde:	360mm
Høyde:	21mm
Bredde:	30mm
Vekt:	0,3kg
Omgivelsestemperatur [°C]:	-25 - 50