



## PRODUCT SHEET

Driver 250-700mA cc (15-24/50V) LCA 17W one4All SR PRE DALI

Art. no: 28000670

**Ledpro**  
by NORLUX

# Driver 250-700mA cc (15-24/50V) LCA 17W one4All SR



### SPECIFICATIONS

System Effekt [W]:	17W
Dimming:	CLO, Corridor, DALI2, Push, Ready2Mains
CC eller CV:	CC
CC [mA]:	250 - 700mA
CC (driver spenning ut) [V]:	15 - 50V
Strøm Toleranse [%]:	3%
Strøm Ripple [%]:	5%
Strøminnstilling:	DALI-2, I-Select 2 Plug (Tridonic), Ready2Ma
Forventet Levetid:	100000h
Isolasjonsklasse:	1 or 2
Dimming Minimum Level :	1%
Dimming output type:	Amplitude Modulation
Maks belastning per kurs - B10:	22
Maks belastning per kurs - B16:	36
Maks belastning per kurs - C10:	36
Maks belastning per kurs - C16:	60
Lekkasjestrøm [mA]:	0,7mA
Startstrøm I <sub>max</sub> [A]:	18A
Startstrøm tid [μs]:	140μs
Produsent:	Tridonic
Produsent P/N:	28000670 - Driver 250-700mA cc (15-24/50V
Lengde:	200mm
Høyde:	31mm
Bredde:	70mm
Vekt:	0,2kg