



PRODUCT SHEET

Driver 350mA cc 9W (13-26V) Phasecut AcTec

Art. no: D35009NT

Ledpro
by NORLUX

Driver 350mA cc 9W (13-26V) Phasecut AcTec

Dimbar LED driver for konstant strøm (350mA) 9W.
Faseavsnitt dim.



SPECIFICATIONS

System Effekt [W]:	9W
Dimming:	Fasekutt
CC eller CV:	CC
CC [mA]:	350 - mA
CC (driver spenning ut) [V]:	13 - 26V
Maks Spenning ut [V]:	31
Strøm Toleranse [%]:	5%
Strøm Ripple [%]:	50%
Forventet Levetid:	30000h
Spenning [V]:	230V 50Hz V
Isolasjonsklasse:	2
Dimming Minimum Level :	1%
Dimming Phasecut Type:	Leading / Trailing edge
Maks belastning per kurs - B10:	35
Maks belastning per kurs - B16:	56
Maks belastning per kurs - C10:	74
Maks belastning per kurs - C16:	118
Lekkasjestrøm [mA]:	0,7mA
Startstrøm I _{max} [A]:	5A
Startstrøm tid [μs]:	300μs
Produsent:	AcTEC
Produsent P/N:	D35009NT - Driver 350mA 9W (13-26V) Phas
Lengde:	109mm
Høyde:	22mm
Bredde:	40mm
Vekt:	0,07kg