



## PRODUCT SHEET

Driver 700mA cc 12W (9-18V) Phasecut AcTec JB&SM

Art. no: D70012NTF-02

# Driver 700mA cc 12W (9-18V) Phasecut AcTec JB&SM



### SPECIFICATIONS

System Effekt [W]:	12W
CC eller CV:	CC
CC [mA]:	700 - mA
CC (driver spenning ut) [V]:	9 - 18V
Maks Spenning ut [V]:	26
Strøm Toleranse [%]:	5%
Strøm Ripple [%]:	50%
Forventet Levetid:	30000h
Spenning [V]:	230V 50Hz V
Isolasjonsklasse:	2
Dimming Minimum Level :	1%
Dimming Phasecut Type:	Leading / Trailing edge
Maks belastning per kurs - B10:	35
Maks belastning per kurs - B16:	56
Maks belastning per kurs - C10:	74
Maks belastning per kurs - C16:	118
Startstrøm I <sub>max</sub> [A]:	5A
Startstrøm tid [μs]:	300μs
Produsent:	AcTEC
Produsent P/N:	D70012NT - Driver 700mA cc 12W (9-18V) Ph
Tilkobling Primær:	Hurtigkobling (L+N)
Tilkobling Sekundær:	SM kontakt
Lengde:	109mm
Høyde:	22mm
Bredde:	40mm
Vekt:	0,1kg