



## PRODUCT SHEET

Driver 24V cv 100W 1-4ch. DALI DT6 SR (TW/RGB/RGBW)

Art. no: W7101

**Ledpro**  
by NORLUX

# Driver 24V cv 100W 1-4ch. DALI DT6 SR (TW/RGB/RGB)

Independent digital dimmable LED-driver for constant voltage 24 VDC Supports DALI-2 specification (IEC 62386-207:2018) Select between 1-4 addressable DALI channels DALI-address can easily be set with integrated display (no programming needed) Optimal for Tunable White, RGB and RGBW applications High resolution dimming range 0.1 100 % Max. output power 100 W (24 VDC)



IP20

### SPECIFICATIONS

System Effekt [W]:	100W
Dimming:	DALI, DALI2
Output Hz:	500
CC eller CV:	CV
CV (driver) [V]:	24V
Strøm Ripple [%]:	3%
Forventet Levetid:	50000h
Isolasjonsklasse:	2
Dimming Minimum Level :	0,1%
Dimming output type:	PWM
Maks belastning per kurs - C10:	16
Maks belastning per kurs - C16:	26
Startstrøm I <sub>max</sub> [A]:	80A
Produsent:	Welight
Farge :	Hvit
Lengde:	244mm
Høyde:	64mm
Bredde:	32mm
Vekt:	0,44kg
Omgivelsestemperatur [°C]:	-2 - 45