



PRODUCT SHEET

Driver 700mA cc 15W (10-21V) Phasecut JB&SM

Art. no: AS-15-700TF-02

Ledpro
by NORLUX

Driver 700mA cc 15W (10-21V) Phasecut JB&SM



SPECIFICATIONS

| | |
|----------------------------------|--|
| System Effekt [W]: | 15W |
| Dimming: | Fasekutt |
| CC eller CV: | CC |
| CC [mA]: | 700 - mA |
| CC (driver spenning ut) [V]: | 10 - 21V |
| Maks Spenning ut [V]: | 29 |
| Strøm Toleranse [%]: | 5% |
| Strøm Ripple [%]: | 20% |
| Strøminnstilling: | Ingen |
| Forventet Levetid: | 50000h |
| Spenning [V]: | 230V 50Hz V |
| Isolasjonsklasse: | 2 |
| Dimming Minimum Level : | 1% |
| Dimming Phasecut Type: | Leading / Trailing edge |
| Maks belastning per kurs - B10: | 140 |
| Maks belastning per kurs - B16: | 224 |
| Maks belastning per kurs - C10: | 280 |
| Maks belastning per kurs - C16: | 448 |
| Startstrøm I _{max} [A]: | 5A |
| Startstrøm tid [μs]: | 100μs |
| Produsent: | AcTEC |
| Produsent P/N: | AS-15-700TF - Driver 700mA cc 15W (10-21V) |
| Tilkobling Primær: | Hurtigkobling |
| Tilkobling Sekundær: | SM kontakt |
| Lengde: | 85mm |
| Høyde: | 22mm |
| Bredde: | 40,4mm |



PRODUCT SHEET

Driver 700mA cc 15W (10-21V) Phasecut JB&SM

Art. no: AS-15-700TF-02



Vekt:

0,05kg