




## FDV SPEC SHEET

Heka 1050lm 830 30° 15W Brushed Steel Phasecut  
Art. no: 2560-30-1

**Ledpro**  
by NORLUX



# Heka 1050lm 830 30° 15W Brushed Steel Phasecut



Art. no: 2560-30-1

### LYS TEKNISK

Lumen LED (tc=25):	1050
Spredningsvinkel [°]:	30°
Fargetemperatur [K]:	3000
Fargegjengivelse [CRI/Ra]:	80
Fargekode:	830
Fargetoleranse [SDCM]:	3
Optikk:	Klar

### MONTERING / TILKOBLING

Tilkobling:	Kabel 2m
Montering:	Innfelt, Bakke

### PRODUKT

IP-grad:	IP67
Vandal klasse:	IK10
Driftstemperatur [°C]:	-20 - 50
Farge :	Børstet Stål
Høyde [mm]:	250
Bredde [mm]:	230
Vekt [kg]:	3,5

### ELEKTRISK DATA

Dimmetype:	Fasekutt
Systemeffekt [W]:	15
Spennning [V]:	230V 50Hz
Isolasjonsklasse:	1
Maks belastning pr kurs - B10:	49
Maks belastning pr kurs - B16:	80
Maks belastning pr kurs - C10:	80
Maks belastning pr kurs - C16:	135
Lekkasjestrøm [mA]:	5
Startstrøm I <sub>max</sub> [A]:	80
Startstrøm tid [µs]:	350
Sokkel :	N/A