



PRODUCT SHEET

Driver On/Off 900mA Panel max 40W 22-44V 18i3 Male/EPN0034

Art. no: 0300-24

Ledpro
by NORLUX

Driver On/Off 900mA Panel max 40W 22-44V 18i3 Mal

On/Offdriver for Panel

Max 45W

900mA

22-40V

Primærside 18i3 male kobling

Sekundærside EPN0034 kobling



SPECIFICATIONS	
System Effekt [W]:	40W
Dimming:	Ingen
Output Hz:	60000
Flicker metric (Pst LM) <:	1
Stroboscopic effect metric (SVM) <:	0,4
CC eller CV:	CC
CC [mA]:	900 - mA
CC (driver spenning ut) [V]:	22 - 44V
Strømnstilling:	Ingen
Spenning [V]:	230V 50Hz V
Isolasjonsklasse:	2
Maks belastning per kurs - B10:	8
Maks belastning per kurs - B16:	14
Maks belastning per kurs - C10:	18
Maks belastning per kurs - C16:	29
Startstrøm I _{max} [A]:	20A
Startstrøm tid [µs]:	300µs
Produsent:	AcTEC
Tilkobling Primær:	18i3 hann
Tilkobling Sekundær:	EPN0034 hunn
Lengde:	127mm
Høyde:	28mm
Bredde:	43mm
Vekt:	0,12kg