



## PRODUCT SHEET

Driver 700mA cc 15W (10-21V) Phasecut JB&SM

Art. no: AS-15-700TF-02

Ledpro  
by NORLUX

# Driver 700mA cc 15W (10-21V) Phasecut JB&SM



### SPECIFICATIONS

System Effekt [W]:	15W
Dimming:	Faseavsnitt
CC eller CV:	CC
CC [mA]:	700 - mA
CC (driver spenning ut) [V]:	10 - 21V
Maks Spenning ut [V]:	29
Strøm Toleranse [%]:	5%
Strøm Ripple [%]:	20%
Strøminnstilling:	Ingen
Forventet Levetid:	50000h
Spenning [V]:	230V 50Hz V
Isolasjonsklasse:	2
Dimming Minimum Level :	1%
Dimming Phasecut Type:	Leading / Trailing edge
Maks belastning per kurs - B10:	140
Maks belastning per kurs - B16:	224
Maks belastning per kurs - C10:	280
Maks belastning per kurs - C16:	448
Startstrøm I <sub>max</sub> [A]:	5A
Startstrøm tid [μs]:	100μs
Produsent:	AcTEC
Produsent P/N:	AS-15-700TF - Driver 700mA cc 15W (10-21V)
Tilkobling Primær:	Hurtigkobling
Tilkobling Sekundær:	SM kontakt
Lengde:	85mm
Høyde:	22mm
Bredde:	40,4mm



## PRODUCT SHEET

Driver 700mA cc 15W (10-21V) Phasecut JB&SM

Art. no: AS-15-700TF-02



Vekt:

0,05kg