



PRODUCT SHEET

Driver 350-1050mA cc (10-46V) 45W DT8 DALI TW 2-ch 18i5 DALI

Art. no: IEM45D-TW-01



Driver 350-1050mA cc (10-46V) 45W DT8 DALI TW 2-ch



SPECIFICATIONS

System Effekt [W]:	38W
Flicker metric (Pst LM) <:	1
Stroboscopic effect metric (SVM) <:	0,4
CC eller CV:	CC
CC [mA]:	350 - 1050mA
CC (driver spenning ut) [V]:	20 - 50V
Maks Spenning ut [V]:	60
Strøm Toleranse [%]:	3%
Strøm Ripple [%]:	2%
Forventet Levetid:	100000h
Isolasjonsklasse:	1 or 2
Dimming Minimum Level :	2%
Maks belastning per kurs - B10:	10
Maks belastning per kurs - B16:	16
Maks belastning per kurs - C10:	16
Maks belastning per kurs - C16:	26
Lekkasjestrøm [mA]:	0,5mA
Startstrøm I _{max} [A]:	26A
Startstrøm tid [μs]:	224μs
Produsent:	Tridonic
Farge :	Hvit
Lengde:	135mm
Høyde:	72mm
Bredde:	24mm
Vekt:	0,19kg