



PRODUCT SHEET

Driver on/off 600mA 25-13W 18i3 male/EPN0034

Art. no: 0300-44



Driver on/off 600mA 25-13W 18i3 male/EPN0034



SPECIFICATIONS

System Effekt [W]:	25-13W
Dimming:	Ingen
Standby power Psb (W) <:	0,5
Flicker metric (Pst LM) <:	1
Stroboscopic effect metric (SVM) <:	0,4
CC eller CV:	CC
CV (driver) [V]:	33V
CC [mA]:	300 - 620mA
CC (driver spenning ut) [V]:	30 - 40V
Maks Spenning ut [V]:	40
Strøm Toleranse [%]:	5%
Strøm Ripple [%]:	5%
Forventet Levetid:	50000h
Spenning [V]:	230V 50Hz V
Isolasjonsklasse:	2
Maks belastning per kurs - B10:	48
Maks belastning per kurs - B16:	76
Maks belastning per kurs - C10:	48
Maks belastning per kurs - C16:	76
Lekkasjestrøm [mA]:	0,5mA
Startstrøm I _{max} [A]:	22,2A
Startstrøm tid [μs]:	53μs
Produsent:	Up-Shine
Tilkobling Primær:	18i3 hann
Tilkobling Sekundær:	EPN0034 hunn
Farge :	Hvit