



PRODUCT SHEET

Driver Dali 650mA Max 29W 28-42V 18i5/EPN0034

Art. no: 0300-52



Driver Dali 650mA Max 29W 28-42V 18i5/EPN0034



SPECIFICATIONS

System Effekt [W]:	28W
Dimming:	DALI2
Standby power P _{sb} (W) <:	0,5
Flicker metric (P _{st} LM) <:	1
Stroboscopic effect metric (SVM) <:	0,4
CC eller CV:	CC
CV (driver) [V]:	33V
CC [mA]:	300 - 750mA
CC (driver spenning ut) [V]:	6 - 42V
Maks Spenning ut [V]:	42
Strøm Toleranse [%]:	5%
Strøm Ripple [%]:	5%
Forventet Levetid:	100000h
Spenning [V]:	230V 50Hz V
Isolasjonsklasse:	2
Dimming Minimum Level :	1%
Dimming output type:	Amplitude Modulation
Maks belastning per kurs - B10:	48
Maks belastning per kurs - B16:	77
Maks belastning per kurs - C10:	48
Maks belastning per kurs - C16:	77
Lekkasjestrøm [mA]:	0,7mA
Startstrøm I _{max} [A]:	6,5A
Startstrøm tid [μs]:	194μs
Produsent:	Boke
Tilkobling Primær:	18i5 DALI hann
Tilkobling Sekundær:	EPN0034 hunn