



PRODUCT SHEET

Driver on/off 700mA 30-18W 18i3 male/EPN0034

Art. no: 0300-47



Driver on/off 700mA 30-18W 18i3 male/EPN0034



SPECIFICATIONS

System Effekt [W]:	30-18W
Dimming:	Ingen
Standby power P _{sb} (W) <:	0,5
Flicker metric (P _{st} LM) <:	1
Stroboscopic effect metric (SVM) <:	0,4
CC eller CV:	CC
CV (driver) [V]:	33V
CC [mA]:	450 - 750mA
CC (driver spenning ut) [V]:	30 - 40V
Maks Spenning ut [V]:	40
Strøm Toleranse [%]:	5%
Strøm Ripple [%]:	5%
Forventet Levetid:	50000h
Spenning [V]:	230V 50Hz V
Isolasjonsklasse:	2
Maks belastning per kurs - B10:	39
Maks belastning per kurs - B16:	63
Maks belastning per kurs - C10:	39
Maks belastning per kurs - C16:	63
Lekkasjestrøm [mA]:	0,5mA
Startstrøm I _{max} [A]:	23,2A
Startstrøm tid [μs]:	224μs
Produsent:	Up-Shine
Tilkobling Primær:	18i3 hann
Tilkobling Sekundær:	EPN0034 hunn