



FDV SPEC SHEET

NSW M Pro Dual 2300lm 2700K-6500K RGBWW 30W 24° Recessed BK

Art. no: 103240-24-2



NSW M Pro Dual 2300lm 2700K-6500K RGBWW 30W 24



Art. no: 103240-24-2

LYS TEKNISK

Lyskilde :	LED (innebygget)
Lumen ut (lm):	2300
Lumen LED (tc=25):	2500
Spredningsvinkel [°]:	24°
Fargetemperatur [K]:	2700-6500K
Fargegjengivelse [CRI/Ra]:	90
Fargekode:	RGBW
Fargetoleranse [SDCM]:	3
Optikk:	Lens

ELEKTRISK DATA

UGR (<=):	7
Dimmetype:	AIOT or APP (Bluetooth connected)
Flimmerfri:	Ja
Systemeffekt [W]:	30
Spenning [V]:	230V 50Hz
Isolasjonsklasse:	2
Strøm LED [mA]:	720
Spenning LED Min [V]:	36
Spenning LED Max [V]:	36

MONTERING / TILKOBLING

Tilkobling:	Hurtigkobling
Utsparring [mm]:	110
Montering:	Innfelt



FDV SPEC SHEET

NSW M Pro Dual 2300lm 2700K-6500K RGBWW 30W 24° Recessed BK

Art. no: 103240-24-2



PRODUKT

Monteres rett i isolasjon:	No
IP-grad:	IP20
Vandal klasse:	IK06
Driftstemperatur [°C]:	-10 - 30
Forventet Levetid :	L80B10: 100 000
Farge :	Sort
RAL:	RAL7021
Høyde [mm]:	175
Bredde [mm]:	118
Diameter [mm]:	118
Vekt [kg]:	1,125