



FDV SPEC SHEET

NSW K Pro Dual 2700lm 2700K-6500K RGBWW 35W 24° 3-Cir BK

Art. no: 103250-24-2



NSW K Pro Dual 2700lm 2700K-6500K RGBWW 35W 24



Art. no: 103250-24-2

LYS TEKNISK

Lyskilde:	LED (innebygget)
Lumen ut (lm):	2500
Lumen LED (tc=25):	2700
Spredningsvinkel [°]:	24°
Fargetemperatur [K]:	2700-6500K
Fargegjengivelse [CRI/Ra]:	90
Fargekode:	RGBW
Fargetoleranse [SDCM]:	3
Optikk:	Lens
UGR (<=):	10

MONTERING / TILKOBLING

Tilkobling:	Skinne 3-Tenning
Montering:	Skinne, Tak

ELEKTRISK DATA

Dimmetype:	AIOT or APP (Bluetooth connected)
Flimmerfri:	Ja
Systemeffekt [W]:	35
Spenning [V]:	230V 50Hz
Isolasjonsklasse:	2
Strøm LED [mA]:	850
Spenning LED Min [V]:	36
Spenning LED Max [V]:	36



FDV SPEC SHEET

NSW K Pro Dual 2700lm 2700K-6500K RGBWW 35W 24° 3-Cir BK

Art. no: 103250-24-2



PRODUKT

IP-grad:	IP20
Vandal klasse:	IK06
Driftstemperatur [°C]:	-10 - 30
Forventet Levetid :	L80B10: 100 000
Farge :	Sort
RAL:	RAL7021
Høyde [mm]:	181
Bredde [mm]:	80
Diameter [mm]:	80
Vekt [kg]:	1