



FDV SPEC SHEET

Panel Circle 6050lm 840 Opal 39W WH 1m cable w/18i3

Art. no: 0794-01-3



Panel Circle 6050lm 840 Opal 39W WH 1m cable w/18i



Art. no: 0794-01-3

LYS TEKNISK

Lyskilde :	LED (innebygget)
Lumen ut (lm):	4770
Lumen LED (tc=25):	6050
Spredningsvinkel [°]:	106x106°
Fargetemperatur [K]:	4000
Fargegjengivelse [CRI/Ra]:	80
Fargekode:	840
Optikk:	Opal

MONTERING / TILKOBLING

Tilkobling:	18i3 Hurtigkobling
Montering:	Innfelt, Tak

PRODUKT

IP-grad:	IP40
Vandal klasse:	IK05
Forventet Levetid :	L80B10: 100 000
Farge :	Hvit
Lengde [mm]:	595
Høyde [mm]:	70
Bredde [mm]:	595
Vekt [kg]:	3

ELEKTRISK DATA

Dimmetype:	Ingen
Systemeffekt [W]:	39
Spennning [V]:	230V 50Hz
Isolasjonsklasse:	1
Maks belastning pr kurs - B10:	31
Maks belastning pr kurs - B16:	50
Maks belastning pr kurs - C10:	46
Maks belastning pr kurs - C16:	73
Startstrøm I _{max} [A]:	5
Startstrøm tid [µs]:	50
Strøm LED [mA]:	950