




FDV SPEC SHEET

Giulio G2 4W 3000K recessed flexible copper/antique brass

Art. no: 102860-13

Ledpro
by NORLUX



Giulio G2 4W 3000K recessed flexible copper/antique



Art. no: 102860-13

LYS TEKNISK

Lyskilde :	LED (innebygget)
Lumen ut (lm):	153
Lumen LED (tc=25):	160
Spredningsvinkel [°]:	24°
Fargetemperatur [K]:	3000
Fargegjengivelse [CRI/Ra]:	90
Fargekode:	830
Fargetoleranse [SDCM]:	3
Optikk:	Lens
UGR (<=):	10

MONTERING / TILKOBLING

Tilkobling:	Terminal
Utsparring [mm]:	Ø48
Montering:	Innfelt, Vegg

ELEKTRISK DATA

Dimmetype:	Touch dim
Flimmerfri:	Ja
Standby power Psb (W) <:	0,1
Flicker metric (Pst LM) <:	1
Stroboscopic effect metric (SVM) <	0,4
Systemeffekt [W]:	4
Spenning [V]:	230V 50Hz
Isolasjonsklasse:	2
Maks belastning pr kurs - B10:	7
Maks belastning pr kurs - B16:	11
Maks belastning pr kurs - C10:	12
Maks belastning pr kurs - C16:	18
Lekkasjestrøm [mA]:	0,7
Startstrøm I _{max} [A]:	20
Startstrøm tid [µs]:	250
Sokkel :	N/A
Strøm LED [mA]:	700
Spenning LED Min [V]:	3



FDV SPEC SHEET

Giulio G2 4W 3000K recessed flexible copper/antique brass

Art. no: 102860-13



PRODUKT

IP-grad:	IP20
Vandal klasse:	IK08
Farge :	Kobber/Messing
Lengde [mm]:	443
Diameter [mm]:	85
Vekt [kg]:	0,4
Hoved Materiale:	Aluminium
Diffusere Materiale:	PMMA
Materiale 2:	Steel