



## FDV SPEC SHEET

Halo Pendant 5000lm 830 120° 43W Gold/White Phasecut Ø120cm

Art. no: 1128-2-120-9



# Halo Pendant 5000lm 830 120° 43W Gold/White Phas



Art. no: 1128-2-120-9

### LYS TEKNISK

Lyskilde:	LED (innebygget)
Lumen ut (lm):	2200
Lumen LED (tc=25):	5050
Spredningsvinkel [°]:	120
Fargetemperatur [K]:	3000
Fargegjengivelse [CRI/Ra]:	80
Fargekode:	830
Fargetoleranse [SDCM]:	6
Optikk:	Frosted
UGR (<=):	16

### MONTERING / TILKOBLING

Tilkobling:	18i3 Hurtigkobling
Montering:	Pendel, Tak

### ELEKTRISK DATA

Dimmetype:	Faseavsnitt
Dimming Output Type:	Amplitude Modulation
Dimming Phasecut Type:	Leading / Trailing edge
Flicker metric (Pst LM) <:	1
Stroboscopic effect metric (SVM) <	0,4
Systemeffekt [W]:	43
Spenning [V]:	230V 50Hz
Isolasjonsklasse:	2
Maks belastning pr kurs - B10:	35
Maks belastning pr kurs - B16:	57
Maks belastning pr kurs - C10:	35
Maks belastning pr kurs - C16:	57
Lekkasjestrøm [mA]:	5
Startstrøm I <sub>max</sub> [A]:	5
Startstrøm tid [µs]:	100
Spenning LED Min [V]:	2,6
Spenning LED Max [V]:	3,4



## FDV SPEC SHEET

Halo Pendant 5000lm 830 120° 43W Gold/White Phasecut Ø120cm

Art. no: 1128-2-120-9



### PRODUKT

IP-grad:	IP20
Driftstemperatur [°C]:	-20 - 45
Forventet Levetid :	L80B10: 100 000
Farge :	Gull/Hvit
Høyde [mm]:	34
Bredde [mm]:	1200
Vekt [kg]:	3