



PRODUCT SHEET

Driver On/Off 600mA max 25W 30-42V 18i3 Male/ EPN0034

Art. no: 0300-2-09



Driver On/Off 600mA max 25W 30-42V 18i3 Male/ EPN



SPECIFICATIONS

System Effekt [W]:	25W
Dimming:	Ingen
Standby power Psb (W) <:	0,5
Flicker metric (Pst LM) <:	1
Stroboscopic effect metric (SVM) <:	0,4
CC eller CV:	CC
CC [mA]:	450 - 600mA
CC (driver spenning ut) [V]:	30 - 42V
Maks Spenning ut [V]:	60
Strøm Toleranse [%]:	8%
Strøm Ripple [%]:	1%
Strømminnstilling:	DIP-switch
Forventet Levetid:	50000h
Spenning [V]:	230V 50HzV
Isolasjonsklasse:	2
Maks belastning per kurs - B10:	66
Maks belastning per kurs - B16:	82
Maks belastning per kurs - C10:	85
Maks belastning per kurs - C16:	155
Lekkasjestrøm [mA]:	0,7mA
Startstrøm I _{max} [A]:	4,4A
Startstrøm tid [µs]:	48µs
Produsent:	Philips
Tilkobling Primær:	18i3 hann
Tilkobling Sekundær:	EPN0034 hunn