



## PRODUCT SHEET

Driver Phasecut 500mA max 25W 25-50V 18i3&EPN0034

Art. no: 0300-28



# Driver Phasecut 500mA max 25W 25-50V 18i3&EPN003



### SPECIFICATIONS

System Effekt [W]:	25W
Dimming:	Faseavsnitt
CC [mA]:	500 - mA
CC (driver spenning ut) [V]:	25 - 50V
Maks Spenning ut [V]:	50
Strøm Toleranse [%]:	5%
Strøm Ripple [%]:	50%
Forventet Levetid:	30000h
Spenning [V]:	230V 50HzV
Isolasjonsklasse:	2
Dimming Minimum Level :	1%
Dimming Phasecut Type:	Leading / Trailing edge
Maks belastning per kurs - B10:	35
Maks belastning per kurs - B16:	56
Maks belastning per kurs - C10:	74
Maks belastning per kurs - C16:	118
Lekkasjestrøm [mA]:	5mA
Startstrøm I <sub>max</sub> [A]:	5A
Startstrøm tid [µs]:	300µs
Produsent:	AcTEC
Produsent P/N:	D50025NT - Driver 500mA 25W (25-50) Phas
Tilkobling Primær:	18i3 hann
Tilkobling Sekundær:	EPN0034 hunn
Lengde:	120mm
Høyde:	28mm
Bredde:	45mm
Vekt:	0,15kg



## PRODUCT SHEET

Driver Phasecut 500mA max 25W 25-50V 18i3&EPN0034

Art. no: 0300-28



Omgivelsestemperatur [°C]:

-20 - 50