



PRODUCT SHEET

Driver DALI 400mA max 24W 20-60V 18i5 DALI/EPN0034

Art. no: 0300-30



Driver DALI 400mA max 24W 20-60V 18i5 DALI/EPN00



SPECIFICATIONS

System Effekt [W]:	25W
Dimming:	DALI
Flicker metric (Pst LM) <:	1
Stroboscopic effect metric (SVM) <:	0,4
CC eller CV:	CC
CC [mA]:	260 - 700mA
CC (driver spenning ut) [V]:	20 - 36V
Maks Spenning ut [V]:	75
Strøm Toleranse [%]:	5%
Strøm Ripple [%]:	40%
Forventet Levetid:	50000h
Spenning [V]:	230V 50HzV
Isolasjonsklasse:	2
Dimming Minimum Level :	1%
Dimming output type:	Amplitude Modulation
Maks belastning per kurs - B10:	11
Maks belastning per kurs - B16:	18
Maks belastning per kurs - C10:	24
Maks belastning per kurs - C16:	39
Lekkasjestrøm [mA]:	0,7mA
Startstrøm I _{max} [A]:	15A
Startstrøm tid [µs]:	300µs
Produsent:	AcTEC
Produsent P/N:	IE25D - Driver 260/350/400/450/500/550/
Tilkobling Primær:	18i5 DALI hann
Tilkobling Sekundær:	EPN0034 hunn
Omgivelsestemperatur [°C]:	-20 - 50