



PRODUCT SHEET

Driver on/off 680mA max 28W 30-40V 18i3/EPN0034

Art. no: 0300-50



Driver on/off 680mA max 28W 30-40V 18i3/EPN0034



SPECIFICATIONS

System Effekt [W]:	28W
Dimming:	Ingen
Output Hz:	50
Standby power Psb (W) <:	0,5
Flicker metric (Pst LM) <:	1
Stroboscopic effect metric (SVM) <:	0,4
CC eller CV:	CC
CV (driver) [V]:	33V
CC [mA]:	646 - 714mA
CC (driver spenning ut) [V]:	30 - 40V
Maks Spenning ut [V]:	40
Strøm Toleranse [%]:	5%
Strøm Ripple [%]:	5%
Forventet Levetid:	50000h
Spenning [V]:	230V 50HzV
Isolasjonsklasse:	2
Maks belastning per kurs - B10:	13
Maks belastning per kurs - B16:	20
Maks belastning per kurs - C10:	21
Maks belastning per kurs - C16:	23
Lekkasjestrøm [mA]:	0,5mA
Startstrøm I _{max} [A]:	28,8A
Startstrøm tid [μs]:	227,2μs
Produsent:	Up-Shine
Tilkobling Primær:	18i3 hann
Tilkobling Sekundær:	EPN0034 hunn