



PRODUCT SHEET

Driver DALI 700mA(250-700) (3-28V) max 20W 18i5 DALI&SM TCI

Art. no: 151403-700-03



Driver DALI 700mA(250-700) (3-28V) max 20W 18i5 DA

Forhåndsinnstilt på 700mA (3-28V)



SPECIFICATIONS

System Effekt [W]:	20W
Dimming:	DALI2
CC eller CV:	CC
CC [mA]:	250 - 700mA
CC (driver spenning ut) [V]:	3 - 49V
Maks Spenning ut [V]:	55
Strøm Ripple [%]:	3%
Strømminnstilling:	DIP-switch
Spenning [V]:	230V 50HzV
Dimming output type:	Amplitude Modulation
Maks belastning per kurs - B10:	31
Maks belastning per kurs - B16:	50
Maks belastning per kurs - C10:	52
Maks belastning per kurs - C16:	85
Startstrøm I _{max} [A]:	5A
Startstrøm tid [μs]:	50μs
Produsent:	TCI
Produsent P/N:	151403 - Mini Jolly DALI 20
Tilkobling Primær:	18i5 DALI hann
Tilkobling Sekundær:	SM kontakt
Lengde:	111mm
Høyde:	22mm
Bredde:	52mm
Omgivelsestemperatur [°C]:	-25 - 45